

RFP No. 08RFP03-FAC is hereby changed as follows:

1. PROPOSAL FORMAT AND CONTENT - Article 3.4, PRICE SHEET

- A. On the second page (Page 17 of 19), indicate written acknowledgment of bidder's receipt of each individual Addenda issued in connection with this Request For Proposal. Failure to so acknowledge receipt of each issued addendum may render bidder's proposal as non-responsive.

2. SPECIFICATIONS - Section 01700, CONTRACT CLOSEOUT

- A. At the bottom of each of the two pages of this Section, correct the page number prefix to read "01700", so that the page numbers for this Section shall read as "01700-1" and "07100-2".

3. SPECIFICATIONS - Section 09680, CARPET

- A. Add new Article 2.07, to read as follows:

"2.07 ADHESIVE RESIDUE ISOLATING-SEALER

- A. Manufacturer: XL Brands, 237 Nance Road, NE, Calhoun, GA 30701; Tel. 800 367-4583 (no substitutions).
- B. High strength latex based compound containing "zero calculated" VOC's and thus below those established by the California SCAQD Rule 1168: XL Brands TRI SEAL."
- B. In Article 3.04, add new Paragraph 3.04 F, to read as follows:
- "F. As an alternative to full removal of all existing carpet adhesive from all floor surfaces, as described in Paragraphs A through E above, the following procedures may be employed:
1. Mechanically remove, by scraping or other suitable and approved means, all existing adhesives, down to the point that no more than a smooth, flat and level condition of thin old adhesive residues remains. "Adhesive residue" is defined as residual staining that is left after all adhesive has been scraped away down to the concrete surface and such that no trowel ridges are any longer present.
 2. No solvents or oily chemicals shall be utilized in this alternative procedure of preparing floor surfaces for the new carpet installation.

3. Apply specified adhesive residue isolating sealer in strict accordance with the manufacturer's instructions. Floors must be clean, dry and free of any wax, oil, paint or other foreign matter that could interfere with a good bond. Apply only when manufacturer's environmental limitations are present. Apply with a 3/8-inch nap paint roller, so as to achieve a 4 mil total film thickness. Application must be made evenly, in two coats, with the second coat applied after the first is dry to the touch (1-2 hours). The second coat should be applied diagonally to the first to ensure good coverage."

END OF ADDENDUM NO. 2